

Gepuntlast gaas
Grillage soudé

Maaswijdte	Draaddikte	Blank staal		Gegalvaniseerd		RVS 304		RVS 316	
Ouverture	Diam. Fil	Acier		Acier galvanisé		Inox AISI 304		Inox AISI 316	
		R	P	R	P	R	P	R	P
6,30	0,80					1200			
6,35	0,60			1000					
7,00	1,00					1000			
8,00	0,80			1000					
8,50	1,00					1000			
12,70	1,05			1020					
12,70	1,05			1220					
12,70	1,60					1000			
19,00	1,45			1020					
19,00	1,45			1220					
20,00	2,50		K						
20,00	2,85						KM		K
21,50	1,50					1000			
24,00	1,60			1220					
25,00	2,00			1020		1000			
25,00	2,85						KMG		K
25,00	3,00		KMG		KMG				
25,40	1,00					1000			
25,40	1,60					1000			
25,40	1,75			1020					
25,40	1,75			1220					
26,00	1,00					1000			
30,00	2,85						KM		KM
30,00	3,00		KMG		KG				
40,00	2,85						KMG		KM
40,00	3,00		MG		M				
40,00	3,80						KM		
40,00	4,00		KMGL		KMGL		KM		K
50,00	2,20						KM		K
50,00	3,00		KMG		S		K		
50,00	3,80						KMG		KM
50,00	4,00		KMGL		KMGL				
50,00	4,80						KM		
50,00	5,00		KMGL		KMGL				K
50,00	6,00		G						
50,80	2,00			1020					
50x25	3,00		K		K				
75,00	5,00		M						
100,00	5,00		L		L				
100,00	6,00		K						
100x50	5,00		L						
200X50	6,00		L						

R = Rolbreedte/largeur du rouleau

P = Plaat/Tôle

K=2000x1000 mm

G=3000x1500 mm

L=3000x2000 mm

M=2500x1250 mm

S=3600x2100 mm